



ANGELUS VITAL SIGNS MONITOR

This easy to use portable vital signs monitor provides proven performance with advanced technology. You can expect both of continuous monitoring and spot check in various setting range of ICU, CCU, transport, ambulatory, local clinic and etc. The large-bright LED and simple menu make the ANGELUS easy to read and use. The ANGELUS monitors two parameters, SpO2 and blood pressure, accurately. It is easy to use and handy to transport the device from one patient to the other.



The ANGELUS flexible fixing system makes easy to place anywhere you need a vital signs monitor.

Features

- SPO2, Pulse Rate, NIBP, Temperature (temperature probes not included)
- Easy to use, accurate and reliable
- Rugged, portable, light weight
- Large LED displays, easy to read
- Suitable for Adult, Paediatric and Neonate
- 24 hours of trend
- Cost effective
- Long-life internal rechargeable battery for uninterrupted monitoring

CODE	DESCRIPTION
MVSA	ANGELUS VITAL SIGNS MONITOR
MVSAFS-01	SPO2 FINGER SENSOR FOR MVSA
MVSPD-0S4-A	TEMPERATURE PROBE FOR MVSA CENTRAL PROBE ADULT 2.75M
MVSPD-RA4-A	TEMPERATURE PROBE FOR MVSA RECTAL PROBE ADULT 2.75M
MBSPD-S18-A	TEMPERATURE PROBE FOR MVSA SURFACE PROBE ADULT 2.75M





ANGELUS VITAL SIGNS MONITOR

Technical Specifications

SPO2 %	Measuring Range	0-100%	
	Accuracy	±1% (90-100%)	
		±2% (80-89%)	
		±3% (65-79%)	
		Unspecified (below 64%)	
Pulse	Measuring Range	25-255 bpm	
	Accuracy	±1%	
NIBP	Measuring Range	Adult	30-300 mmHg
		Neonate	15-150 mmHg
	Accuracy	±3 mmHg or 2%	
	Maximum Pressure	Adult	300+30 mmHg
		Neonate	150+15 mmHg
Indicator	Indicator	3 Digit Dual Colour FND 4EA (SPO2, HR, NIBP)	
		4 Digit FND (Time)	
		10-BAR LED 1EA (Amplitude)	
Trend	48hours		
Alarm	SPO2, HR, NIBP (Sys., Dia., MAP)		
Power	External Power	AC100-240V, 50/60Hz	
		DC12-28V, 3A	
	Batteries	Rechargeable battery 1.2VX6ea, 2.5AH	
	Battery Running Time	2.5hours	
	FUSE	240V 2A X2ea	
General Condition	Maximum Consumption Power	≤15W (35VA-45VA)	
	Dimension	200 (W) X 170 (H) X 100 (D) mm	
	Weight	1.3 kg	
	Operating Temperature	0 to +50°C	
	Storage Temperature	-20°C to +60°C	
Safety Classification	ANGELUS	Class IIb; BF APPLIED PART	
Warranty	2 years for main unit, 1 year for sensor		

ANGELUS TEMPERATURE PROBES

